


PLASKOLITE

**POLYGAL®
MULTIWALL POLYCARBONATE
SHEETS AND CONNECTION
SYSTEMS**





Polygal | MultiWall Sheets

THE ART OF LIGHT MANAGEMENT

Great artists know how to work with light. Great architects and designers look for the best materials to bring the light into each space to create the right atmosphere. PLASKOLITE produces a range of flexible multiwall thermoplastic sheets that are ideal for roofing, glazing, skylights, signage and interior design projects. They maximize the available light and provide insulation and UV-protection, as well as adding texture and color to your project.

Polygal MultiWall sheets are constructed from multiple layers of polycarbonate for maximum strength, with an internal cellular structure that makes them light and flexible.

Features and Benefits

- Excellent insulation
- Controlled daylight transmission
- Virtually unbreakable
- Flexible and easy to install
- Flame retardant
- Lightweight
- UV-blocking
- Environmentally friendly



A



B



A Agriculture - maximizing natural light and outstanding insulation all year round.

B Architecture - lightweight roofing with selective layers for light management.

C Decorative - creative design features with many color and illumination options.

D Signage - lightweight material with optimum light diffusion for lightbox signs.




D

Double and triple layered sheets

Double and triple layered Polygal MultiWall sheets are manufactured in various colors and degrees of transparency.

The sheets are designed for use in most conventional roofing and glazing applications.



Thermogal

Thermogal's unique interior X-brace combines extra strength and rigidity with outstanding insulation. Ideal for low-pitched roofs and closed structures with large-span openings, Thermogal is available in various thicknesses, widths, and colors.



Selectogal

An exclusive PLASKOLITE patent lets Selectogal (RFX) control heat and light transmission into buildings, thereby reducing heating and lighting costs.

Selectogal's prismatic structure reflects most of the sun's heat in the summer and allows for increase in solar heat in the winter.















Titan Sky

Titan Sky's internal cross-brace structure gives these sheets twice the strength and rigidity of equivalent standard polycarbonate sheets. PLASKOLITE Titan Sky provides an advanced solution that stands up to heavy loads.



Mechanical and thermal properties

Product	Structure	Thickness (mm,in)	Weight (g/m ² , lb/ft ²)	Standard Width (mm, in)	Minimum Radius for Cold Bending Arches (m, ft)	U-Factor* (W/m ² x °C, BTU/hr/ ft ² x °F)	Light Transmission (%)**			
							Bronze	NGL	Clear	Ice
Double and triple layered sheets		4, 0.157	800, 0.16	980, 39 1050, 41 1200, 47 1220, 48 1250, 49 2100, 83	0.7, 2.3	3.9, 0.69	42	-	82	32
		6, 0.236	1300, 0.27		1.05, 3.4	3.6, 0.63	42	-	80	32
		8, 0.315	1500, 0.31		1.4, 4.6	3.3, 0.58	42	25	80	32
		10, 0.394	1700, 0.35		1.75, 5.7	3.0, 0.53	42	25	79	32
		16, 0.625	2700, 0.55		2.8, 9.2	2.3, 0.41	42	35	72	32
Titan sky		10, 0.394	1750, 0.36	1050, 41 1200, 47	1.75, 5.7	2.4, 0.42	42	25	62	32
		16, 0.625	2500, 0.51	2100, 83	2.8, 9.2	2.1, 0.37	42	25	61	32
Selectogal		16, 0.625	3000, 0.61	1050, 41 1200, 47	2.8, 9.2	2.3, 0.41	42	32	68	-
Thermogal		20, 0.787	3000, 0.61	1200, 47 2100, 83	3.6, 11.8	1.9, 0.33	20	20	56	20
		25, 0.984	3500, 0.72		4.4, 14.4	1.7, 0.30	20	20 (51***)	55	20 (54***)
		32, 1.26	3800, 0.78	980, 39 1200, 47	5.6, 18.4	1.3, 0.23	15	15 (47***)	50	15
Thermogal super		32, 1.26	3800, 0.78		Not recommended	1.06, 0.19	-	10	38	-

| * ASTM C177 TNO | ** ASTM D1003 | ***ASTM D1494



Available In Standard Colors	Standard Sheet Length	Thermal Expansion	Service Temp. Range
Clear, Ice, Nonglare (NGL), Blue, Bronze, Gray, Green, Turquoise	3m/9.8ft, 4m/13.1ft, 6m/19.7ft Max. length: in accordance with handling restrictions	2.5 mm/m (0.03in/ft): Clear, Ice and NGL 4.5 mm/m (0.054in/ft): dark colors (ΔT=80°C / ΔT=176°F)	-40°C-+120°C (-13°F to +185°F) for short time service, -25°C to +85°C (-13°F to 185°F) for prolonged service

CONNECTION PROFILES AND ACCESSORIES

Our interconnecting polycarbonate or aluminum profiles connect multiple multiwall sheets to cover large areas. They do not add weight and lie flush with the sheets. The connectors are UV-resistant and provide excellent sealing for roofs and inclined walls, because they do not obstruct light at connection points. These profiles are available in unlimited lengths, are easy to handle and install, and suit most roofing, curtain wall and cladding applications


RECOMMENDED USES

Plaskolite profiles are suitable for most roofing, curtain wall, and cladding applications.




ECP connection system

The easy clip profile system is for polycarbonate profiles designed to connect multiwall polycarbonate sheets with thicknesses between 6mm to 10mm (0.236" to 0.394"). Profiles can easily be connected together to form reliable joints. Manufactured in standard colors, in lengths of 6m or 12m (19.7' or 39.4')..




Combined connection System

This system consists of an aluminum base and polycarbonate cap profiles. Designed to connect multiwall polycarbonate sheets with a thicknesses between 6mm to 18mm (0.236" to 0.709"), it provides a rigid connection. Manufactured in standard colors, and lengths up to 6M (19.7').




GCP System

The gasket clip profile system for polycarbonate profiles with integrated co-extruded gaskets, designed to connect multiwall polycarbonate sheets with thicknesses between 6mm to 10mm (0.236" to 0.394"). It provides a well sealed connection, manufactures in standard colors and lengths of 6m as 12m (19.7' and 39.4').




MGL System

The mega lock profile glazing system designed to connect multiwall polycarbonate sheets with thicknesses between 6mm to 16mm (0.236" to 0.625"). It provides a rigid and sealed connection in lengths up to 6m (19.7').




SELECTIVE LAYERS

POLYSHADE




Designed for warm climates, Polyshade reflects sunlight to prevent excess heat build up for effective control of solar heat.

PRIMALITE




These unique sheets selectively reflect most of the near-IR solar radiation and transmit more visible light. Available in various colors and degrees of transparency.

SILHOUETTE




Silhouette, with its sophisticated and lustrous exterior surface, radiates elegance and style and features outstanding reflective qualities and light selectivity. Available in Pearland Gold.

POLYCOOLITE




Specifically designed to let in natural light for photosynthesis, Polycoolite blocks harmful UV rays, supplies high blues and reds, and reflects heat from the unused green.

SPRING



Spring, a transparent sheet with a special coextrusion layer on the exterior side (under its UV protective layer), blocks invisible IR solar radiation and heat.

RAINBOW



Special optical effects in Rainbow sheets combine with the angle of light to change the sheet color (for example, from red to green) to harmonize with any setting.

Optical Properties Of Selective Layers

Selective Layer	Structure	Thickness (mm,in)	Light Trans. (%)		Shading Coefficient
			ASTM D1003	ASTM D1494	
Polylite Polyshade	Double and triple layered sheets	8-10 (0.315-0.394)	18	24	0.33
		16 (0.625)	18	20	0.26
Primalite	Double and triple layered sheets	8-10 (0.315-0.394)	45	68	0.45
	Double and triple layered sheets	16 (0.625)	32	-	0.31
	Titan Sky	16 (0.625)	18	-	0.27
	Thermogal	25 (0.984)	18	-	0.34
	Thermogal	32 (1.26)	15	-	0.28
Silhouette Pearl	Titan Sky	10 (0.394)	40	-	0.58
	Titan Sky	16 (0.625)	18	-	0.35
	Thermogal	32 (1.26)	10	45	0.39
Silhouette Gold	Double and triple layered sheets	8-10 (0.315-0.394)	35	63	0.42
	Titan Sky	16 (0.625)	18	47	0.29
	Thermogal	32 (1.26)	10	43	0.31
Polycoolite	Double and triple layered sheets	8 (0.315)	45	63	0.50
Spring	Double and triple layered sheets	8 (0.315)	70	-	0.61
	Thermogal	32 (1.26)	44	47	0.42
Rainbow	Double and triple layered sheets	8 (0.315)	15	-	0.60

PLASKOLITE

A GLOBAL LEADER IN THE PRODUCTION OF THERMOPLASTIC SHEET

FOUNDED IN 1950

Our Mission: to deliver superior thermoplastic sheet, coatings and polymers to the world, through long-lasting customer relationships and hands-on customer service.

MANUFACTURING LOCATIONS



From our founding, PLASKOLITE strives to treat our employees, our customers, our community and the world, with kindness, dignity and respect. This drives our continuing effort to create sustainable products, in a sustainable manner, for future generations. This on-going commitment is expressed in the

PLASKOLITE Sustainable Ecosystem:

QUICK FACTS

STATUS: Privately held


GLOBAL HEADQUARTERS: Columbus, OH

EMPLOYEES: 1800 Worldwide

MARKETS SERVED: Signage, Lighting, Retail Display, Construction, Transportation, Security, Bath & Spa, Industrial, Architecture, Green Houses

OUR PILLARS OF SUSTAINABILITY

EACH CONTRIBUTES TO MAKING THE WORLD A BETTER PLACE



WHAT WE MAKE

Versatile, high-quality, durable thermoplastic materials...not single-use plastics

HOW IT'S MADE

How we make our products reflects our overall philosophy of continuous environmental improvement

HOW IT'S USED

Our thermoplastics play an important role in advancing human well-being, energy conservation and quality of life

These suggestions and data are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of use are beyond our control. We recommend that the prospective user determines the suitability of our materials and suggestions before adopting them on a commercial scale.

© 2023 PLASKOLITE, LLC 102023
POLYGAL® is a registered trademark of PLASKOLITE LLC

PLASKOLITE

400 W Nationwide Blvd, Suite 400
Columbus, OH 43215
800.848.9124 • Fax: 877.538.0754
plaskolite@plaskolite.com
www.plaskolite.com

BRO101_PGL_MW